



Dimensions	35S11/13/14 HR				35S18 HR			
	3000	3000L	3300	3950	3000	3000L	3300	3950
A Wheelbase	3000	3000L	3300	3950	3000	3000L	3300	3950
Roof	HR	HR	HR	HR	HR	HR	HR	HR
B Overall length	5077	5477	5997	7012	5077	5477	5997	7012
C Front overhang	998	998	998	998	998	998	998	998
D Rear overhang	1079	1479	1699	2064	1079	1479	1699	2064
E Overall width	1996	1996	1996	1996	1996	1996	1996	1996
K Overall height (unladen)	2645	2645	2640	2670	2645	2645	2640	2670
S Rear floor height	695	695	695	695	695	695	695	695
with opt. rear air susp. - raised	645+40	645+40	645+40	645+40	645+40	645+40	645+40	645+40
with opt. rear air susp. - lowered	645-60	645-60	645-60	645-60	645-60	645-60	645-60	645-60
Turning circle (k to k) (m)	10.4	10.4	11.2	13.1	10.4	10.4	11.2	13.1
Turning circle (w to w) (m)	11.5	11.5	12.4	14.3	11.5	11.5	12.4	14.3

Cargo Area								
Internal length (Standard)	2600	3000	3520	4560	2600	3000	3520	4560
Internal width	1800	1800	1800	1800	1800	1800	1800	1800
Internal height	1900	1900	1900	1900	1900	1900	1900	1900
Width between wheelarches	1320	1320	1320	1320	1320	1320	1320	1320
Length (from rr. edge of seat backrests)*	1585	1985	2505	3520	1585	1985	2505	3520
Length (from rr. edge of seat anchoring frame)*	1850	2250	2770	3785	1850	2250	2770	3785

Load Access								
Rear door opening width	1540	1540	1540	1540	1540	1540	1540	1540
Rear door opening height	1780	1780	1780	1780	1780	1780	1780	1780
Rear door opening angle (deg)	180	270	270	270	180	270	270	270
Side door opening width	1100	1100	1250	1250	1100	1100	1250	1250
Side opening height	1780	1780	1780	1780	1780	1780	1780	1780

Weights (kg)								
Kerb weights are with full fuel tank, oil, water, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.								
Wheelbase	3000	3000L	3300	3950	3000	3000L	3300	3950
GVW	3500	3500	3500	3500	3500	3500	3500	3500
GTW	6300	6300	6300	6300	6300	6300	6300	6300
Kerb weights								
Front axle - with opt. seats	1285	1255	1275	1330	1325	1295	1315	1370
Rear axle - with opt. seats	835	910	960	1030	830	905	960	1020
Total	2120	2165	2235	2360	2155	2200	2275	2390
Maximum Payload - with opt seats	1380	1335	1265	1140	1345	1300	1225	1110
Plated weights								
Front axle	1800	1800	1800	1800	1800	1800	1800	1800
Rear axle	2240	2240	2240	2240	2240	2240	2240	2240



35S11/13/14/18 SemiWindow Crew VAN



Engines	S11	S13	S14	S18
Fuel	Diesel	Diesel	Diesel	Diesel
Capacity (litres)	2.3	2.3	2.3	3.0
Cylinders	4 (16 valves)			
Emission Compliance	Euro 4			
Fuel System	Common rail Generation 2			
Power (hp/ kW)	106/ 78	126/ 93	136/ 100	176/ 130
@ rpm	2750-3900 3050-3600 3000-3900 3200-3500			
Torque (Nm/ lbft)	270/ 199	290/ 213	320/ 236	400/ 295
@ rpm	1800-2750 1650-3050 1700-3000 1250-3000			
Exhaust system	Side emit - RHS			

Gearboxes	S11	S13	S14	S18
Type	5S300OD	5S300OD	5S300OD	6S400OD
	5 speed	5 speed	5 speed	6 speed
	Synchronmesh			
	Overdrive			
Ist gear	4.99 : 1	4.99 : 1	4.99 : 1	5.37 : 1
Top gear	0.78 : 1	0.78 : 1	0.78 : 1	0.79 : 1

Performance for HR Models

Gear	Ist	Top	Ist	Top	Ist	Top	Ist	Top
Max. geared speed (mph)	16	102	15	94	17	106	16	112
Gradeability @ GVW (%)	40+	6	40+	7	40+	7	40+	8

Rear Axle Ratios

Std. with HR	3.91	3.91	3.73	3.15
--------------	------	------	------	------

Clutch	S11	S13	S14	S18
Type	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Diameter	267	267	267	280

Electrics

Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah
13 pin towing electrics (.13/.14/.18 engines only)	

Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension

Front	Independent with transverse leaf spring
Rear	Parabolic leaf spring
Anti-roll Bar	Standard on rear
Shock absorbers	Front and rear

Brakes

Front / diameter	Ventilated disc brakes / 300 mm
Rear / diameter	Disc brakes / 296 mm
ESP 8	Standard
<i>(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)</i>	
Parking brake	On rear axle

Steering

Power assisted - Rack & Pinion

Wheels & Tyres

Wheels	6JK 16
Tyres	225/65R16
Spare	Option

Fuel Tank

70 litres on nearside with locking fuel cap

Standard Equipment

Cab

Drivers airbag with seat belt pretensioners
Dual passenger seat with headrests
Fully adjustable driver's seat with headrest
Large dual storage pockets in doors
Three point inertia reel belt on all seats
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Underseat storage
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder
Lighting to rear compartment

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph
Coolant temperature indicator
Speedometer
Rev.counter
3 DIN drawers, two of which carry CD Player and/or tachograph
LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Full bulkhead with sliding window behind driver (deleted when 2nd row of seats is specified)
Unglazed rear doors
Steering lock

Load Area

Side load door with sliding window and sliding window opposite side load door
Provision in floor for optional 3 person bench seat with 3 point seat belts
Floor - steel ribbed with load lashing rings
Sides - reinforced with load lashing rings
Side access via top hung side sliding door with internal step and grab handle
Rear access by hinged doors with stops at 90 and 270 degrees (90 and 180 degrees on 3000 wheelbase) and grab handle
Interior lights at side and rear (door operated with individual isolation)

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full cathodic protection dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Options

AGile automated 6-speed gearbox
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
Air conditioning
Alarm system to cab and load area
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
Blue Tooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
ECAS air suspension on rear axle
Exhaust with particulate trap (CRT)
Exterior mirrors - heated and electrically adjustable
Fuel tank with locking cap - 100 litres
GPS satellite navigation
Headlamp washers
Overhead windscreen storage rack and DIN drawer
PVC trim
Rear axle ratio options
Rear camera and spot light
Rear seating - 2nd row 3 person bench seat (M1 tested), 3 point inertia reel seat belts on all seats, wooden floor,

side and roof trim (deletion of bulkhead and lining are mandatory with this option).
Reverse parking sensor integrated into rear step
Spare wheel
Tachograph - digital
Third stop light
Tow bar with ball
Towing electric socket (13 pin) (.11 engine only)

For a complete list of Daily options please contact your local Iveco distributor

DAILY

35S11/13/14/18 Semi Window Crew VAN

IVECO