



Dimensions	35S13 HR		35S13 XHR	
A Wheelbase	3300	3950	3300	3950
Roof	HR	HR	XHR	XHR
B Overall length	5997	7012	5997	7012
C Front overhang	998	998	998	998
D Rear overhang	1699	2064	1699	2064
E Overall width	1996	1996	1996	1996
K Overall height (unladen)	2640	2670	2825	2869
S Rear floor height	695	695	695	695
Turning circle (k to k) (m)	11.2	13.1	11.2	13.1
Turning circle (w to w) (m)	12.4	14.3	12.4	14.3

Cargo Area				
Capacity (m ³)	12.0	15.6	13.2	17.2
Internal length	3520	4560	3520	4560
Internal width	1800	1800	1800	1800
Internal height	1900	1900	2100	2100
Width between wheelarches	1320	1320	1320	1320

Load Access & Plug Door Access				
Rear door opening width	1540	1540	1540	1540
Rear door opening height	1780	1780	1990	1990
Rear door opening angle (deg)	270	270	270	270
Plug door opening width	650	650	650	650
Plug door opening height	1960	1960	2160	2160
Height of 1st step from ground	300	300	300	300
Height of 2nd step from ground	485	485	485	485
Height of 3rd step from ground	705	705	705	705

Weights (kg)				
Kerb weights are with full fuel tank, oil, water, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.				
Wheelbase	3300	3950	3300	3950
GVW	3500	3500	3500	3500
GTW	6300	6300	6300	6300
Kerb weights				
Front axle	1250	1295	1250	1295
Rear axle	890	970	920	1005
Total	2140	2265	2170	2300
Maximum Payload	1360	1235	1330	1200
Plated weights				
Front axle	1800	1800	1800	1800
Rear axle	2240	2240	2240	2240

Engines	S13
Fuel	Diesel
Capacity (litres)	2.3
Cylinders	4 (16 valves)
Emission Compliance	Euro 4
Fuel System	Common rail Generation 2
Power (hp/ kW)	126/ 93
@ rpm	3050-3600
Torque (Nm/ lbft)	290/ 213
@ rpm	1650-3050
Exhaust system	Side emit - RHS

Gearboxes	S13
Type	5S300OD
	5 speed
	Synchromesh
	Overdrive
1st gear	4.99 : 1
Top gear	0.78 : 1

Performance	
Gear	1st Top
Max. geared speed (mph)	15 94
Gradeability @ GVW (%)	40+ 7

Rear Axle Ratios	
Std. with HR & XHR	3.91

Clutch	S13
Type	Hydraulic
Diameter	267

Electrics	
Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah
13 pin towing electrics	

Lighting & Signalling	
Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps	

Suspension	
Front	Independent with transverse leaf spring
Rear	Parabolic leaf spring
Anti-roll Bar	Standard on rear
Shock absorbers	Front and rear

Brakes	
Front / diameter	Ventilated disc brakes / 300 mm
Rear / diameter	Disc brakes / 296 mm
ESP 8	Standard
(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)	
Parking brake	On rear axle

Steering	
Power assisted - Rack & Pinion	

Wheels & Tyres	
Wheels	6JK 16
Tyres	225/65R16
Spare	Option

Fuel Tank	
90 litres on RHS with locking fuel cap	

Standard Equipment

Cab
 Drivers airbag with seat belt pretensioners
 Fully adjustable driver's seat with headrest
 Large dual storage pockets in driver's door
 Three point inertia reel belt on driver's seat
 Single piece floor mat
 Windows electrically operated
 Exterior mirrors with integrated wide angle and direction indicators
 2 cup holders
 Bottle holder
 Glove compartment with added storage
 A4 storage compartment
 Additional in-dash storage
 Cooled compartment (with opt. air conditioning)
 Clip holder
 Unimpeded access to cargo area
 Fully glazed electrically operated plug door

Heating & Ventilation
 Four speed fan with 5 different distribution modes and cab recirculation
 Windshield and side window defrost facility
 Fresh air ventilation when heater turned off

Dashboard incorporates
 Dash-mounted gear lever
 RDS stereo radio/CD player (with Can security)
 Provision for GPS or tachograph
 Coolant temperature indicator
 Speedometer
 Rev.counter
 3 DIN drawers, two of which carry CD Player and/or tachograph
 LCD Display Panel includes: odometer,

Dashboard incorporates (cont'd)
 trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security
 Central locking with remote control and door locking management - anti-theft system
 Engine immobiliser
 Unglazed rear doors
 Ladder type bulkhead behind driver
 Steering lock

Load Area
 Access via a nearside front electric plug door
 Floor - steel ribbed with load lashing rings
 Sides - reinforced with load lashing rings
 Rear access by hinged doors with stops at 90 and 270 degrees and grab handle
 Interior lights at side and rear (door operated with individual isolation)

Construction & Finish
 C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full cathodic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Options

AGile automated 6-speed gearbox
 Air conditioning
 Alternator- heavy duty 180A
 Ambient air temperature gauge (option with air conditioning)
 BlueTooth vivavoice system with steering wheel controls - Blue & me
 Body builder connectors
 Colour keyed bumper and trim
 Exhaust with particulate trap (CRT)
 Exterior mirrors - heated and electrically adjustable
 GPS satellite navigation
 Headlamp washers
 Rear axle ratio options
 Rear camera and spot light
 Reverse parking sensor integrated into rear step
 Spare wheel
 Tachograph - digital
 Third stop light
 Tow bar with ball

For a complete list of Daily options please contact your local Iveco distributor

DAILY

**35S13 Axxess
 VAN**

IVECO