



Dimensions	40C11/13/15/18 LR		40C11/13/15/18HR				40C11/13/15/18 XHR	
A Wheelbase	3000	3000L	3000	3000L	3300	3950	3300	3950
Roof	LR	LR	HR	HR	HR	HR	XHR	XHR
B Overall length	5077	5477	5077	5477	5997	7012	5997	7012
C Front overhang	998	998	998	998	998	998	998	998
D Rear overhang	1079	1479	1079	1479	1699	2064	1699	2064
E Overall width	1996	1996	1996	1996	1996	1996	1996	1996
K Overall height (unladen)	2355	2355	2725	2730	2705	2705	2910	2910
S Rear loading height	735	735	735	735	735	735	735	735
with opt rear air susp - raised	700+70	700+70	700+70	700+70	700+70	700+70	700+70	700+70
with opt rear air susp - lowered	700-50	700-50	700-50	700-50	700-50	700-50	700-50	700-50
Turning circle (k to k) (m)	10.4	10.4	10.4	10.4	11.2	13.1	11.2	13.1
Turning circle (w to w) (m)	11.5	11.5	11.5	11.5	12.4	14.3	12.4	14.3

Cargo Area	40C11/13/15/18 LR		40C11/13/15/18HR				40C11/13/15/18 XHR	
Capacity (m <sup>3</sup> )	7.3	8.3	9.0	10.2	12.0	15.6	13.2	17.2
Internal length	2600	3000	2600	3000	3520	4560	3520	4560
Internal width	1800	1800	1800	1800	1800	1800	1800	1800
Internal height	1545	1545	1900	1900	1900	1900	2100	2100
Width between wheelarches	1030	1030	1030	1030	1030	1030	1030	1030

Load Access	40C11/13/15/18 LR		40C11/13/15/18HR				40C11/13/15/18 XHR	
Rear door opening width	1540	1540	1540	1540	1540	1540	1540	1540
Rear door opening height	1430	1430	1780	1780	1780	1780	1990	1990
Rear door opening angle (deg)	180	270	180	270	270	270	270	270
Side door opening width	1100	1100	1100	1100	1250	1250	1250	1250
Side opening height	1415	1415	1780	1780	1780	1780	1780	1780

Weights (kg)	40C11/13/15/18 LR		40C11/13/15/18HR				40C11/13/15/18 XHR	
<b>Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.</b>								
Wheelbase	3000	3000L	3000	3000L	3300	3950	3300	3950
GVW	4350	4350	4350	4350	4350	4350	4350	4350
GTW	7200	7200	7200	7200	7200	7200	7200	7200
<b>Kerb weights</b>								
Front axle	1330	1300	1320	1295	1320	1360	1320	1360
Rear axle	900	985	930	1045	1070	1175	1100	1195
Total	2230	2285	2250	2340	2390	2535	2420	2555
Maximum Payload	2120	2065	2100	2010	1960	1815	1930	1795
<b>Plated weights</b>								
Front axle	1900	1900	1900	1900	1900	1900	1900	1900
Rear axle	3100	3100	3100	3100	3100	3100	3100	3100

\* For 40C15/18 Models add 25kgs on the front axle and 10kgs on the rear axle

Engines	C11	C13	C15	C18
Fuel	Diesel	Diesel	Diesel	Diesel
Capacity (litres)	2.3	2.3	3.0	3.0
Cylinders	4 (16 valves)			
Emission Compliance	Euro 4			
Fuel System	Common rail Generation 2			
Power (hp/ kW)	106/ 78	126/ 93	146/ 107	176/ 130
@ rpm	2750-3900 3050-3600 3000-3500 3200-3500			
Torque (Nm/ lbft)	270/ 199	290/ 213	350/ 258	400/ 295
@ rpm	1800-2750 1650-3050 1400-2600 1250-3000			
Exhaust system	Side emit - RHS			

Gearboxes	C11	C13	C15	C18
Type	5S300OD	5S300OD	6S400OD	6S400OD
	5 speed	5 speed	6 speed	6 speed
	Synchronmesh			
	Overdrive			
1st gear	4.99 : 1	4.99 : 1	5.37 : 1	5.37 : 1
Top gear	0.78 : 1	0.78 : 1	0.79 : 1	0.79 : 1

#### Performance for HR Models

Gear	Ist	Top	Ist	Top	Ist	Top	Ist	Top
Max. geared speed (mph)	15	94	14	87	16	106	16	106
Gradeability @ GVW (%)	40+	7	40+	7	40+	6	40+	7

#### Rear Axle Ratios

Std. with LR	3.91	3.91	3.308	3.308
Std. with HR & XHR	4.18	4.18	3.308	3.308

Clutch	C11	C13	C15	C18
Type	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Diameter	267	267	280	280

#### Electrics

Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah

#### Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

#### Suspension

Front	Independent with torsion bars
Rear	Parabolic leaf spring
Anti-roll Bar	Front and rear
Shock absorbers	Front and rear

#### Brakes

Front / diameter	Ventilated disc brakes / 290 mm
Rear / diameter	Disc brakes / 289 mm
ESP 8	Standard
(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)	
Parking brake	On rear axle

#### Steering

Power assisted - Rack & Pinion

#### Wheels & Tyres

Wheels	6JK 16
Tyres	195/75R16
Spare	Located behind left wheel arch in rear

#### Fuel Tank

70 litres on nearside with locking fuel cap

## Standard Equipment

#### Cab

Drivers airbag with seat belt pretensioners  
Dual passenger seat with headrests  
Fully adjustable driver's seat with headrest  
Large dual storage pockets in doors  
Three point inertia reel belt on all seats  
Single piece floor mat  
Windows electrically operated  
Exterior mirrors with integrated wide angle and direction indicators  
2 cup holders  
Underseat storage  
Bottle holder  
Glove compartment with added storage  
A4 storage compartment  
Additional in-dash storage  
Cooled compartment (with opt. air conditioning)  
Clip holder

#### Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation  
Windshield and side window defrost facility  
Fresh air ventilation when heater turned off

#### Dashboard incorporates

Dash-mounted gear lever  
RDS stereo radio/CD player (with Can security)  
Provision for GPS or tachograph  
Coolant temperature indicator  
Tachograph - digital  
Rev. counter  
3 DIN drawers, two of which carry CD Player and/or tachograph  
LCD Display Panel includes: odometer, trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

#### Security

Central locking with remote control and door locking management - anti-theft system  
Engine immobiliser  
Unglazed full bulkhead  
Unglazed rear doors  
Steering lock

#### Load Area

Floor - steel ribbed with load lashing rings  
Sides - reinforced with load lashing rings  
Side access via top hung side sliding door with internal step and grab handle  
Rear access by hinged doors with stops at 90 and 270 degrees (90 and 180 degrees on 3000 wheelbase) and grab handle  
Interior lights at side and rear (door operated with individual isolation)

#### Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

## Options

AGile automated 6-speed gearbox  
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)  
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags  
Air conditioning  
Alarm system to cab and load area  
Alternator- heavy duty 180A  
Ambient air temperature gauge (option with air conditioning)  
Blue Tooth vivavoice system with steering wheel controls - Blue & me  
Body builder connectors  
Colour keyed bumper and trim  
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.  
ECAS air suspension on rear axle  
Exhaust with particulate trap (CRT)  
Exterior mirrors - heated and electrically adjustable  
Fuel tank with locking cap - 100 litres  
GPS satellite navigation  
Headlamp washers  
Overhead windscreen storage rack and DIN drawer  
PVC trim  
Rear axle ratio options  
Rear camera and spot light  
Reverse parking sensor integrated into rear step  
Third stop light

Tow bar with ball  
Towing electric socket (13 pin)

For a complete list of Daily options please contact your local Iveco distributor

**DAILY**

**40C11/13/15/18  
VAN**

**IVECO**