



Dimensions	50C15/18 HR	50C15/18 XHR
A Wheelbase	3950	3950
Roof	HR	XHR
B Overall length	7012	7012
C Front overhang	998	998
D Rear overhang	2064	2064
E Overall width	1996	1996
K Overall height (unladen)	2745	2930
S Rear floor height	775	775
Turning circle (k to k) (m)	14.0	14.0
Turning circle (w to w) (m)	15.1	15.1

Cargo Area

Capacity (m ³)	15.6	17.2
Internal length	4560	4560
Internal width	1800	1800
Internal height	1900	2100
Width between wheelarches	1030	1030

Load Access & Plug Door Access

Rear door opening width	1540	1540
Rear door opening height	1780	1990
Rear door opening angle (deg)	270	270
Plug door opening width	650	650
Plug door opening height	1960	2160
Height of 1st step from ground	380	380
Height of 2nd step from ground	565	565
Height of 3rd step from ground	785	785

Weights (kg)

Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.

Wheelbase	3950	3950
GVW	5200	5200
GTW	8700	8700
Kerb weights		
Front axle	1445	1445
Rear axle	1135	1175
Total	2580	2620
Maximum Payload	2620	2580
Plated weights		
Front axle	1900	1900
Rear axle	3700	3700

Engines	C15	C18
Fuel	Diesel	Diesel
Capacity (litres)	3.0	3.0
Cylinders	4 (16 valves)	
Emission Compliance	Euro 4	
Fuel System	Common rail	Generation 2
Power (hp/ kW)	146/ 107	176/ 130
@ rpm	3000-3500	3200-3500
Torque (Nm/ lbft)	350/ 258	400/ 295
@ rpm	1400-2600	1250-3000
Exhaust system	Side emit - RHS	

Gearboxes	C15	C18
Type	6S400OD	6S400OD
	6 speed	6 speed
	Synchromesh	Synchromesh
	Overdrive	Overdrive
1st gear	5.37 : 1	5.37 : 1
Top gear	0.79 : 1	0.79 : 1

Performance

Gear	1st	Top	1st	Top
Max. geared speed (mph) (90kph limiter std.)	14	97	14	97
Gradeability @ GVW (%)	38	5	40+	6

Rear Axle Ratios

Std. with HR & XHR	3.60	3.60
--------------------	------	------

Clutch	C15	C18
Type	Hydraulic	Hydraulic
Diameter	280	280

Electrics

Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah

Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension

Front	Independent with torsion bars
Rear	Parabolic leaf spring
Anti-roll Bar	Front and rear
Shock absorbers	Front and rear

Brakes

Front / diameter	Ventilated disc brakes / 290 mm
Rear / diameter	Disc brakes / 289 mm
ESP 8	Standard
(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)	
Parking brake	On rear axle

Steering

Power assisted - Rack & Pinion

Wheels & Tyres

Wheels	6JK 16
Tyres	195/75R16
Spare	Located behind left wheel arch in rear

Fuel Tank

90 litres on RHS with locking fuel cap

Standard Equipment

Cab

Drivers airbag with seat belt pretensioners
Fully adjustable driver's seat with headrest
Large dual storage pockets in driver's door
Three point inertia reel belt on driver's seat
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder
Unimpeded access to cargo area
Fully glazed electrically operated plug door

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph
Coolant temperature indicator
Tachograph - digital
Rev.counter
3 DIN drawers, two of which carry CD Player and/or tachograph
LCD Display Panel includes: odometer,

Dashboard incorporates (cont'd)

trip computer with distance, time, fuel consumption etc; headlamp orientation (dip/main); clock

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Unglazed rear doors
Ladder type bulkhead behind driver
Steering lock

Load Area

Access via nearside front electric plug door
Floor - steel ribbed with load lashing rings
Sides - reinforced with load lashing rings
Rear access by hinged doors with stops at 90 and 270 degrees and grab handle
Interior lights at side and rear (door operated with individual isolation)

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full cathodic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Options

AGile automated 6-speed gearbox
Air conditioning
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
BlueTooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Exhaust with particulate trap (CRT)
Exterior mirrors - heated and electrically adjustable
GPS satellite navigation
Headlamp washers
Rear axle ratio options
Rear camera and spot light
Reverse parking sensor integrated into rear step
Third stop light
Tow bar with ball
Towing electric socket (13 pin)

For a complete list of Daily options please contact your local Iveco distributor

DAILY

**50C15/18 Axess
VAN**

IVECO