



Dimensions	45C14/17LR		45C14/17HR				45C14/17XHR	
A Wheelbase	3000	3000L	3000	3000L	3300	3950	3300	3950
Roof	LR	LR	HR	HR	HR	HR	XHR	XHR
B Overall length	5077	5477	5077	5477	5997	7012	5997	7012
C Front overhang	998	998	998	998	998	998	998	998
D Rear overhang	1079	1479	1079	1479	1699	2064	1699	2064
E Overall width	1996	1996	1996	1996	1996	1996	1996	1996
K Overall height (unladen)	2365	2365	2735	2740	2745	2745	2930	2930
S Rear loading height	775	775	775	775	775	775	775	775
with opt rear air susp - raised	700+70	700+70	700+70	700+70	700+70	700+70	700+70	700+70
with opt rear air susp - lowered	700-50	700-50	700-50	700-50	700-50	700-50	700-50	700-50
Turning circle (k to k) (m)	11.0	11.0	11.0	11.0	12.0	14.0	12.0	14.0
Turning circle (w to w) (m)	12.1	12.1	12.1	12.1	13.1	15.1	13.1	15.1

Cargo Area	45C14/17LR		45C14/17HR				45C14/17XHR	
Capacity (m ³)	7.3	8.3	9.0	10.2	12.0	15.6	13.2	17.2
Internal length	2600	3000	2600	3000	3520	4560	3520	4560
Internal width	1800	1800	1800	1800	1800	1800	1800	1800
Internal height	1545	1545	1900	1900	1900	1900	2100	2100
Width between wheelarches	1030	1030	1030	1030	1030	1030	1030	1030

Load Access	45C14/17LR		45C14/17HR				45C14/17XHR	
Rear door opening width	1540	1540	1540	1540	1540	1540	1540	1540
Rear door opening height	1430	1430	1780	1780	1780	1780	1990	1990
Rear door opening angle (deg)	180	270	180	270	270	270	270	270
Side door opening width	1100	1100	1100	1100	1250	1250	1250	1250
Side opening height	1415	1415	1780	1780	1780	1780	1780	1780

Weights (kg)	45C14/17LR		45C14/17HR				45C14/17XHR	
Kerb weights are with full fuel tank, oil, water, spare wheel, tools and include driver @ 75kgs. Kerb weights are subject to a manufacturing tolerance of + 5%.								
Wheelbase	3000	3000L	3000	3000L	3300	3950	3300	3950
GVW	4600	4600	4600	4600	4600	4600	4600	4600
GTW	8100	8100	8100	8100	8100	8100	8100	8100
Kerb weights								
Front axle	1385	1350	1385	1350	1370	1425	1370	1425
Rear axle	900	980	925	1005	1065	1145	1095	1185
Total	2285	2330	2310	2335	2435	2570	2465	2610
Maximum Payload	2315	2270	2290	2245	2165	2030	2135	1990
Plated weights								
Front axle	1900	1900	1900	1900	1900	1900	1900	1900
Rear axle	3400	3400	3400	3400	3400	3400	3400	3400

Engines	C14	C17
Fuel	Diesel	Diesel
Capacity (litres)	3.0	3.0
Cylinders	4 (16 valves)	
Emission Compliance	EEV	
Fuel System	Common rail Generation 2	
Power (hp/ kW)	140/ 103	170/ 125
@ rpm	2800-3500	2990-3500
Torque (Nm/ lbft)	350/ 258	400/ 295
@ rpm	1250-2800	1250-2990
Exhaust system	Side emit - RHS	
Exhaust with CRT	Standard	

Gearboxes	C14	C17
Type	6S400OD	6S400OD
	6 speed	6 speed
	Synchromesh	
	Overdrive	
1st gear	5.37 : 1	5.37 : 1
Top gear	0.79 : 1	0.79 : 1

Performance

Gear	1st	Top	1st	Top
Max. geared speed (mph) (90kph limiter std.)	14	97	14	97
Gradeability @ GVW (%)	40+	6	40+	7

Rear Axle Ratios

Std. with LR, HR & XHR	3.60	3.60
------------------------	------	------

Clutch	C14	C17
Type	Hydraulic	Hydraulic
Diameter	280	280

Standard Equipment

Cab

Drivers airbag with seat belt pretensioners
Dual passenger seat with headrests
Fully adjustable driver's seat with headrest
Large dual storage pockets in doors
Three point inertia reel belt on all seats
Single piece floor mat
Windows electrically operated
Exterior mirrors with integrated wide angle and direction indicators
2 cup holders
Undersat storage
Bottle holder
Glove compartment with added storage
A4 storage compartment
Additional in-dash storage
Cooled compartment (with opt. air conditioning)
Clip holder

Heating & Ventilation

Four speed fan with 5 different distribution modes and cab recirculation
Windshield and side window defrost facility
Fresh air ventilation when heater turned off

Dashboard incorporates

Dash-mounted gear lever
RDS stereo radio/CD player (with Can security)
Provision for GPS or tachograph
Coolant temperature indicator
Tachograph - digital
Rev.counter
3 DIN drawers, two of which carry CD Player and/or tachograph
Comfort LCD Display Panel
(See description under Options)

Security

Central locking with remote control and door locking management - anti-theft system
Engine immobiliser
Unglazed full bulkhead
Unglazed rear doors
Steering lock

Load Area

Floor - steel ribbed with load lashing rings
Sides - reinforced with load lashing rings
Side access via top hung side sliding door with internal step and grab handle
Rear access by hinged doors with stops at 90 and 270 degrees (90 and 180 degrees on 3000 wheelbase) and grab handle
Interior lights at side and rear (door operated with individual isolation)

Construction & Finish

C-section steel longitudinal side members and tubular cross members with pressed steel unitary construction body mounted on rubber bushes. Anti-corrosion protection includes full catheporetic dipping with galvanized boxed sections and strategic use of zinc plated panels in vulnerable areas. Protective under seal for all under body cabin area, wheel housings and engine area. SMC bumper and side mouldings.

Electrics

Alternator - std	14v - 110A
Alternator - opt	14v - 140A or 180A
Battery	12v - 110Ah

Lighting & Signalling

Halogen headlamps; front fog lamps; twin rear fog lamps; twin reverse lamps

Suspension

Front	Independent with torsion bars
Rear	Parabolic leaf spring
Anti-roll Bar	Front and rear
Shock absorbers	Front and rear

Brakes

Front / diameter	Ventilated disc brakes / 290 mm
Rear / diameter	Disc brakes / 289 mm
ESP 8	Standard
(includes ABS-Anti-Lock Brakes, EBD-Electronic Brake Force Distribution, ASR-Traction Control, MSR-Motor Torque Reduction, HBA-Hydraulic Brake Assist)	
Parking brake	On rear axle

Steering

Power assisted - Rack & Pinion

Wheels & Tyres

Wheels	6JK 16
Tyres	195/75R16
Spare	Located behind left wheel arch in rear

Fuel Tank

70 litres on nearside with locking fuel cap

Options

AGile automated 6-speed gearbox
Dual front passenger airbag with seat belt pretensioners (in addition to std. drivers airbag)
Dual front passenger airbag with seatbelt pretensioners (in addition to std. drivers airbag) and additional driver and passenger window airbags
Air conditioning
Alarm system to cab and load area
Alternator- heavy duty 180A
Ambient air temperature gauge (option with air conditioning)
Blue Tooth vivavoice system with steering wheel controls - Blue & me
Body builder connectors
Colour keyed bumper and trim
Comfort dashboard (Standard with CRT) - LCD panel additions include: dual trip function; servicing indicator; door locking function; speed alarm; fuel economy indicator; external temperature display and ice warning indicator are also shown only when climate control is specified. Automated gearbox information is also displayed when Agile gearbox is specified.
ECAS air suspension on rear axle
Exterior mirrors - heated and electrically adjustable
Fuel tank with locking cap - 100 litres
GPS satellite navigation
Headlamp washers
Overhead windscreen storage rack and DIN drawer
PVC trim
Rear axle ratio options
Rear camera and spot light
Reverse parking sensor integrated into rear step
Third stop light
Tow bar with ball

Towing electric socket (13 pin)

For a complete list of Daily options please contact your local Iveco distributor

ECODAILY 45C14/I7EEV
VAN

IVECO